



Shown with Cradle Mount and optional wings




ON DEMAND SEAL PLATE

SIGNIFICANTLY REDUCES ENERGY CONSUMPTION

FEATURES

- 115 Volt Power Supply
- Self-Regulating Boardless Square Rod for Increased Transversal Rigidity and Consistent Cutting
- Easy to use Photoeye for Accurate Product Detection
- 8" by 15" On-Demand Timer Controlled Heated Seal Plate That Significantly Reduces Power Consumption
- Seal Plate Reaches Seal Temperature Within Seconds
- Thermostatic High Temperature Limit Device
- Thermistor Controlled Circuit That Reduces Power Consumption As Residual Heat Increases In Seal Plate
- GFCI for Improved Circuit Integrity and Protection
- Stainless Steel Front Plate for Easy Wipe Down
- Rigid Aluminum And Stainless Steel Construction Throughout
- Stainless Steel Wrapping Surface
- 20" Maximum Roll Width
- 8" Maximum Roll Diameter
- Supplied With A Replaceable Non-Stick Cover to Maintain A Hygienic Seal Surface
- Splash Guard
- Utility Rebates may be Available

MODEL SPECS

MODEL	200ESC	200ESA
FILM MOUNT	NEW Cradle System	Axle System
FILM CAPACITY	20"	
SEAL PLATE	8" x 15"	
WORKING HEIGHT	Adjustable Height, Standard 31"	
OVERALL DIMENSIONS	24" D, 25" W, 36" H Standard (61 D, 63.5 W, 92 H cm)	
POWER REQUIREMENT	115 Volt, 16 Amp, 60Hz  20A breaker, compatible with NEMA 5-20P (shown)	
SHIPPING WEIGHT	90 lbs. (12 kg)	

AVAILABLE OPTIONS

- 6" x 15" Hot Plate
- Axle or Cradle Film Mount
- All Stainless Steel Wing, 14" x 22" (R/L)
- Accessory Storage Rack
- All Stainless Steel Construction